

SAFETY DATA SHEET

5530 PART A

Page 1

Issued: 05/01/2007

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 5530 PART A

Product code: 5530A

Company name: Holdtite Adhesives

Shadon Way

Portobello Industrial Estate

Birtley

Co. Durham

DH3 2RE

Tel: +44(0)191 4113191

Fax: +44(0)191 4113192

Email: andrew.collins@holdtite.com

2. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Danger of cumulative effects. Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: N,N-DIMETHYL-P-TOLUIDINE [1] N,N-DIMETHYL-M-TOLUIDINE [2]

N,N-DIMETHYL-O-TOLUIDINE [3] 1-10%

EINECS: 202-805-4 CAS: 99-97-8

[T] R23/24/25; [Xn] R33; [-] R52/53

- METHYL METHACRYLATE 30-50%

EINECS: 201-297-1 CAS: 80-62-6

[F] R11; [Xi] R37/38; [Sens.] R43

- METHACRYLIC ACID 1-10%

EINECS: 201-204-4 CAS: 79-41-4

[Xn] R21/22; [C] R35

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: METHYL METHACRYLATE

WEL (8 hr exposure limit): 208 mg/m³ WEL (15 min exposure limit): 416 mg/m³

- METHACRYLIC ACID

WEL (8 hr exposure limit): 72 mg/m³ WEL (15 min exposure limit): 143 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Flash point°C: 20

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: N,N-DIMETHYL-P-TOLUIDINE [1] N,N-DIMETHYL-M-TOLUIDINE [2]
N,N-DIMETHYL-O-TOLUIDINE [3]

IPR MUS LD50 212 mg/kg

- METHYL METHACRYLATE

IPR RAT LD50 1328 mg/kg

ORL MUS LD50 3625 mg/kg

ORL RAT LD50 7872 mg/kg

- METHACRYLIC ACID

ORL MUS LD50 1250 mg/kg

ORL RAT LD50 1600 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SAFETY DATA SHEET

5530 PART A

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1993 **ADR Class:** 3
Packing group: II **Classification code:** F1
Shipping name: FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE)
Labelling: 3 **Hazard ID no:** 33

IMDG / IMO

UN no: 1993 **Class:** 3
Packing group: II **EmS:** F-E,S-E*
Marine pollutant: . **Labelling:** 3

IATA / ICAO

UN no: 1993 **Class:** 3
Packing group: II **Packing instructions:** 305(P&CA); 307(CAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Harmful.



Risk phrases: R11: Highly flammable.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R33: Danger of cumulative effects.

R36/37/38: Irritating to eyes, respiratory system and skin.

R43: May cause sensitisation by skin contact.

Safety phrases: S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe fumes.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S51: Use only in well-ventilated areas.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to

the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R33: Danger of cumulative effects.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R11: Highly flammable.

R37/38: Irritating to respiratory system and skin.

R43: May cause sensitisation by skin contact.

R21/22: Harmful in contact with skin and if swallowed.

R35: Causes severe burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.